


DLT SRV 33 Serie

Full Automatic Three Phase
Servo Voltage Stabilizers
3 - 150 kVA

DELTA Voltage regulators are servo drive structure, microcontroller controlled heavy duty devices which regulates mains voltage for critical loads.

SINGLE PHASE 110-115-120-127-220-230-240 VAC
THREE PHASE 220-230 240-380-400-415-440 VAC
IP20, IP21, IP54, Versions Available



Technical Specifications

- DELTA SRV33 series are three phase voltage stabilizers regulate mains voltage and bring many advantages.
- Non-linear charges drive
- 3 phase input 3 phase output
- Wide power and voltage interval
- Fast Regulation
- High reliability thanks to Microprocessor and Smart Driver
- High efficiency
- Load transfer to Bypass via pole charge switch
- Safe and economic usage
- Overload protection
- Digitally displayed status, input & output measurements
- 2 years warranty
- 10 years spare parts support

Specifications

MODEL	33003	33006	33010	330015	330020	330030	330045	330060	330075	330100	330120	330150
Power kVA	3	6	10,5	15	22,5	30	45	60	75	100	120	150
REGULATOR INPUT												
In.Vol.Correct.Interval	275 - 450 VAC [Optional: 190-415VAC]											
Operation Frequency	47...65 Hz											
Line Input Protection	Overcurrent, Low and High voltage protection											
REGULATOR OUTPUT												
Output Voltage	380 / 400 / 415 VAC RMS ± %1											
Overloading	10 Sec. % 200 Load											
Correction Speed	~ 90 Volt / Sec.											
Upturn Period	~ 90 Volt / Sec. (160 VAC - 250 VAC)											
Output Protection	Protects load by opening the circuit when overburden, short circuit occurs.											
WORKING PRINCIPLE												
	Servo Motor, Microprocessor Controlled, Full Automatic											
GENERAL												
Cooling	Smart Fan System											
Measured Value Monitor.	DELTA TRUE RMS Panel Voltmeter (74x74 mm) output voltage and line voltage monitorization											
Total Harmonic Distortion	-											
Total Efficiency	> % 96											
Mechanical By-Pass	“Manually Controlled Line - PAKO SWITCH Selects Voltage Regulator” Switch Turn On / Off											
Protection Level	IP 20											
ENVIRONMENTAL												
Working Temperature	-10 °C / 50 °C											
Storage Temperature	- 25 °C / +60 °C											
Relative Humidity	< % 90, DIN (40040)											
Working Altitude	< 2000 m.											
Acoustic Level	< 50 dB											
Documents	CE // TÜV Austria Hellas (ISO 9001)											
DIMENSIONS (cm)												
HxWxD (cm)	110 x 40 x 63				119 x 40 x 63			140 x 88 x 60			165 x 93 x 65	
Weight (kg)	75	85	95	105	125	145	165	260	280	310	400	425

